

## Combitube 12D Range

T: +44 (0)1621 874200  
 F: +44 (0)1621 874299

### Product Information Sheet

Issue: 01 Date: 14.08.13

**DESCRIPTION** Extruded biopolymer and oxo-bio polypropylene tube which protects and helps establish trees

**APPLICATION** For the protection of trees against animal browsing, herbicide spray and for the improvement of growth through a microclimate

**SECTORS** Forestry and Horticulture



		TUBEX Combitube 12D Range		TUBEX Combitube Plus 12D Range		
<b>Dimensions</b>						
Height	m	0.75	1.2	1.2	1.5	1.8
Diameter	mm	73–105	73–105	80–120	80–120	80–120
No of ties		2	2	2	2	2
Type of tie		Releasable	Releasable	Releasable	Releasable	Releasable
Size of tie	inch	9	9	10	10	10
Top tie height (+ tolerance)	mm	452–472	865–885	810–840	1160–1190	1310–1345
Bottom tie height (+ tolerance)	mm	190–210	235 - 265	265 - 265	235 - 265	235–265
Bottom height of holes	mm	350	450	450	450	450
No of holes		3 x 100mm bands	5 x 100mm bands	5 x 100mm bands	7 x 100mm bands	9 x 100mm bands
Av. Weight per tube	g	91	148	177	221	265.5
<b>Packaging</b>						
Nest		5	5	5	5	5
Bundle		100	100	60	60	60
Bag or strap banded		Bag	Strap Banded	Strap Banded	Strap Banded	Strap Banded

Material	For all sizes
Tube	Biopolymer +oxo-bio polypropylene
Tie	Nylon
Colour	Green
Service Life	Approx. 5 years
Degradability	Biodegradable + Oxo-biodegradable
Manufacturing tolerance	- 2.5cm
Recommended support	Stake

\*If you require other sizes that are not specified within this data sheet please get in contact.

As part of its continual improvement process Fiberweb Geosynthetics Ltd reserve the right to change the properties listed on this data sheet without prior notice.

TM indicates a trade mark of Fiberweb plc or a Fiberweb Group company, many of which are registered in a number of countries around the world.

The data contained herein is supported by scientific research carried out in controlled environments. The performance of Tubex 12D is reliant on numerous factors which are outside Fiberweb's control (such as the environment conditions local to the tube's location) and for which Fiberweb cannot be held responsible. For this reason Fiberweb makes no warranty or representation as to the performance of Tubex 12D and disclaims all warranties and representations whether express or implied to the maximum extent permitted by law.